



Research on Hybrid Solar Photovoltaic/Thermal (PV/T) System

[Link to publication record in Manchester Research Explorer](#)

Citation for published version (APA):

Sundaram, S., Paul, M., & Mahmoudi Larimi, Y. (in press). Research on Hybrid Solar Photovoltaic/Thermal (PV/T) System. *Energies*.

Published in:

Energies

Citing this paper

Please note that where the full-text provided on Manchester Research Explorer is the Author Accepted Manuscript or Proof version this may differ from the final Published version. If citing, it is advised that you check and use the publisher's definitive version.

General rights

Copyright and moral rights for the publications made accessible in the Research Explorer are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

Takedown policy

If you believe that this document breaches copyright please refer to the University of Manchester's Takedown Procedures [<http://man.ac.uk/04Y6Bo>] or contact uml.scholarlycommunications@manchester.ac.uk providing relevant details, so we can investigate your claim.



Research on Hybrid Solar Photovoltaic/Thermal (PV/T) System

Senthilarasu Sundaram¹, **Manosh Paul**² and **Yasser Mahmoudi**^{3,*}

- 1 Environment and Sustainability Institute, University of Exeter, Penryn Campus, Cornwall TR10 9FE, UK (s.sundaram@exeter.ac.uk)
 - 2 James Watt School of Engineering, University of Glasgow, Glasgow, G12 8QQ, UK (manosh.paul@glasgow.ac.uk)
 - 3 Department of Mechanical, Aerospace and Civil Engineering, The University of Manchester, Manchester, M13 9PL, UK (yasser.mahmoudilarimi@manchester.ac.uk)
- * Authors to whom correspondence should be addressed

Introduction

The present day buildings have become the third largest consumer of energy after industry and agriculture and energy consumption in buildings contributing up to 40% of the total energy use in developed countries. Energy consumption is rapidly increasing as the growth of population, urbanization, and demands of building services and comfort levels. Thus, reducing building energy consumption plays a very important role in controlling global energy demand and mitigating climate change.

A useful measure to reduce building energy use is hybrid photovoltaic/thermal (PV/T) system. PV/T panels combine two well-established renewable energy technologies, solar photovoltaics modules and solar thermal collectors, into one integrated component that removes generated heat from the solar photovoltaics thereby improving electrical efficiencies [1, 2]. The electrical performance of more recently installed PV/T systems does show an overall increase in the annual electrical energy output of 4%-12% in comparison with solar PV systems in the same situation. Using PV/T the generation potential per square meter can be substantially increased. This is particularly advantageous when space for installation can be limited, such as on domestic roofs. In some systems, it is possible to obtain the same energy output as a side-by-side installation of solar PV and solar thermal in 40% less area. PV/T systems can also integrate with energy-use equipment, such as heat pumps and absorption chillers, to provide heating or cooling for buildings [1]. Moreover, solar thermal and power technologies can also integrate with distributed energy storage systems and building demand response technologies to improve the flexibility and reliability of both utility grid and buildings.

This Special Issue presents a collection of original articles and case studies focusing on investment an economic benefits of solar photovoltaic systems, performance assessment, cooling and temperature control, as well as integration of solar photovoltaic technology with other renewable systems.

Overview of Contributions to the Special Issue

This Special Issue comprehends 4 research articles, with the scope investigated being mainly representative of the UK, EU, South Korea and Saudi Arabia. A brief description and discussion

of the contributions to this Issue is reported in this section. It is worth noting that the order in which the contributions are presented does not imply any judgment of merit and it is dictated only by narrative purposes.

Solar PV panels are typically 20% efficient and significant fraction of the absorbed sunlight rays are converted into heat. The generated heat increases the temperature of the panel, resulting in a decrease in the electrical efficiency and consequently a poor economic scenario. In this regard Haidar et al. [1] performed a comprehensive experimental and modelling studies on cooling of PV panels using evaporative cooling (EC) principle. A new EC design to cool the bottom surface of a PV panel was fabricated, tested, and modelled in order to assess the effectiveness of the EC method for solar PVs. A series of experimentation under realistic outdoor conditions was performed in Riyadh-Saudi Arabia in July. To better understand the cooling process of the PV panel and performing a detailed parametric study a steady state heat and mass transfer model was implemented and compared with the experimental data. Their results showed that the uncooled PV panel temperature can reach to about 73 °C, while the temperature of the evaporative cooled panel do not exceed 65 °C (over 10 °C cooling using the proposed cooling technique). This has resulted in an average efficiency gain of 6.7% and power output improvement of 5%. Additionally, they observed that the evaporative cooling reduced the PV temperature fluctuation, which results in a better regulation of electrical power output and reduces the uncertainty associated with solar PV systems.

Kim et al. [2] studied Building-Integrated PVT (BIPVT) systems which can simultaneously produce electrical and heat energy for buildings that require heating, and offer higher solar energy use per unit area of installation than conventional BIPV systems. They designed, and built a new air-type PVT collector with perforated baffles and conducted outdoor experimental tests to assess the performance of the proposed system. The tests were performed in April to May 2020 in Cheonan-South Korea under a radiation intensity of at least 700 W/m² on the inclined plane and varying inlet/outlet air flow rates of 100, 150, and 200 m³/h. They found that the thermal efficiency of the proposed air-type PVT collector was 47% at an air flow of 200 m³/h. During peak solar radiation of about 950 W/m², the thermal efficiency was between 34.7% and 49.9% for the flow rate in the range of 100–200 m³/h. The electrical efficiency of the system dropped from 16.6% to 16.1% when the PV module rear temperature rose from 44 °C to 52 °C. Under the outside temperature range of 21 °C–31 °C and radiation of 825 W/m²–958 W/m², the electrical efficiency decreased by 0.375% for every 1 °C increase in PV module rear temperature. Their exergy analysis showed that the total exergy efficiency of the air-type PVT collector with perforated baffles is 24.8%–30.5% is almost half of the total energy efficiency which is 44.1%–63.3%.

Eko and Paul [3] analysed integration of solar photovoltaic systems with other energy sources in sub-Saharan Africa-Malawi region in order to address a key research question of “How can the low electricity access rate in Malawi be addressed?” They considered integration of multiple possible off grid, integrated, sustainable energy systems based on locally available energy resources including solar photovoltaic, wind turbine, diesel generators and battery storage. The multiyear and sensitivity analysis function of HOMER Pro microgrid simulation software is used to analyse the off grid performance of the proposed integrated system to provide electricity for an estimate of 400 households in Machinga Boma, a community in the

Southern region of Malawi. They found that among various integrated systems, the system comprises of Solar Photovoltaic array (750 kWp), Diesel generator (460 kW) and 3000 kWh nominal capacity battery bank is the most optimal system with an overall energy cost of USD 0.339/kWh. Based on the cost simulation result, the lithium-ion battery component accounts for 49% of the total system initial capital cost of the proposed system. While the USD 0.339 is in line with other literature, the electricity tariffs in Malawi for residential and non-residential use are USD 0.13/kWh and USD0.16/kWh, respectively. This means that the reposed hybrid energy system offers a higher price per kWh of electricity, possibly due to the inclusion of a diesel generator and battery storage in the system. While technically feasible, the high hybrid system energy cost poses a constraint on the rate of acceptance of the system by the users, due to the familiarity of a lower cost per kWh (tariff structure) in Malawi. Finally, in comparison to a diesel generator only system, their proposed hybrid system is significantly more environmentally benign, producing CO₂ of only 10% of the average CO₂ produced by a diesel system. The environmental impact of the system is an essential consideration, especially as the Malawian energy policy goal centres on reducing the dependence on traditional biomass and traditional fuels.

Using a panel data approach, Tomczak et al. [4] determined whether investing in so-called “green” companies that are associated with the production of photovoltaic (PV) components offers a greater return on investment relative to investing in “red” companies that do not manufacture PV components. They used a sample for the period of 2015–2018, and applied a new approach to panel data for the sector taking into account 92 ratios derived from balance sheet, profit and loss account, cash flow, and market value data. They deployed the Classification Trees, the k-Nearest Neighbors methods and Altman model to investigate whether companies that manufacture solar modules, solar cells, solar silicon rods, solar wafers, solar power, solar photovoltaic products, and related equipment (green companies) can be differentiated from other enterprises in the sector that are not associated with renewable energy and whether these companies are in a better financial state. Their analysis showed that the green companies can be distinguished from red companies at classification accuracies of 90%, 86% and 93% for the Chi-squared Automatic Interaction Detector (CHAID), Classification and Regression Trees (CRT), and k-Nearest Neighbors algorithms, respectively. On the basis of an assessment of the financial performance of enterprises using two variants of the Altman model, they conclude that red enterprises perform better financially relative to green enterprises. Such a finding was in agreement with the recent literature who suggest that investing in green companies is not lucrative and going green does not pay and/or that fossil fuel companies tend to perform better financially. However, green enterprises exhibit an upward trend in ratios, as indicated by an analysis of crucial ratios. This finding implies that in the near future, financial indicators for green companies may equal or exceed those of red companies, if this upward trend continues. Importantly, this suggests that the profitability of green companies is increasing and thus, investing in green companies has the potential for profitability.

Funding: This research received no external funding.

Conflicts of Interest: The authors declare no conflict of interest.

Acknowledgments: The Editors are grateful to all authors and reviewers for their outstanding work and support in fulfilling the proposed goal of this Special Issue.

Conflicts of Interest: The author declares no conflict of interest.

References

1. Obalanlege, M.A.; Mahmoudi, Y.; Douglas, R.; Bailie, D.; Davidson, J. Experimental assessment of short cycling in a hybrid photovoltaic-thermal heat pump system. *Applied Energy* **2020**, *268*, 114916.
2. Obalanlege, M.A.; Mahmoudi, Y.; Douglas, R.; Ebrahimnia-Bajestan, E.; Bailie, D.; Davidson, J. Performance assessment of a hybrid photovoltaic-thermal and heat pump system for solar heating and electricity. *Renewable Energy* **2020**, *148*, 558-572.
3. Haidar, Z.A.; Orfi, J.; Kaneesamkandi, Z. Photovoltaic Panels Temperature Regulation Using Evaporative Cooling Principle: Detailed Theoretical and Real Operating Conditions Experimental Approaches. *Energies* **2021**, *14*, 145. <https://doi.org/10.3390/en14010145>.
4. Kim, J.-H.; Yu, J.-S.; Kim, J.-T. An Experimental Study on the Energy and Exergy Performance of an Air-Type PVT Collector with Perforated Baffle. *Energies* **2021**, *14*, 2919. <https://doi.org/10.3390/en14102919>.
5. Eko, J.O.; Paul, M.C. Integrated Sustainable Energy for Sub-Saharan Africa: A Case Study of Machinga Boma in Malawi. *Energies* **2021**, *14*, 6330. <https://doi.org/10.3390/en14196330>
6. Tomczak, S.K.; Skowrońska-Szmer, A.; Szczygielski, J.J. Is It Possible to Make Money on Investing in Companies Manufacturing Solar Components? A Panel Data Approach. *Energies* **2021**, *14*, 3406. <https://doi.org/10.3390/en14123406>.